

TABULAR DESCRIPTION

RNP RWY 24

Serial Number	Path Descriptor	Waypoint Identifier	Fly-Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed limit (Kt)	VPA/TCH (°/m)	Navigation Specification
010	IF	KL509	—	—	—	—	—	+4200	-230	—	RNP APCH
020	TF	KL506	—	328(328.2)	—	6.0	—	+3800	-230	—	RNP APCH
010	IF	KL510	—	—	—	—	—	+4200	-230	—	RNP APCH
020	TF	KL506	—	148(148.2)	—	6.0	—	+3800	-230	—	RNP APCH
010	IF	KL506	—	—	—	—	—	+3800	-230	—	RNP APCH
020	TF	KL507	—	238(238.2)	—	5.0	—	@3200	—	—	RNP APCH
030	TF	RW24	Y	238(238.2)	0	5.3	—	@1508	—	3.0/15	RNP APCH
010	IF	RW24	—	—	0	—	—	—	—	—	RNP APCH
020	CF	KL508	Y	238(238.2)	0	3.0	—	—	-230	—	RNP APCH
030	DF	KL509	—	—	—	—	L	—	-230	—	RNP APCH
010	IF	KL506	—	—	—	—	—	+3800	-230	—	RNP APCH
020	HM	KL506	—	238(238.2)	—	—	L	+3800	-230	—	RNP APCH

WAYPOINT LIST

RNP RWY 24

Waypoint Identifier	Coordinates	
KL506	18°30'09.781"N	001°34'37.173"E
KL507	18°27'31.358"N	001°30'08.729"E
KL508	18°23'07.630"N	001°22'42.550"E
KL509	18°25'02.340"N	001°37'56.270"E
KL510	18°35'17.161"N	001°31'17.878"E
RW24	18°24'42.802"N	001°25'23.463"E