

TABULAR DESCRIPTION

RNAV GNSS RWY 12

Serial Number	Path Descriptor	Waypoint Identifier	Fly- Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed limit (Kt)	VPA/TCH	Navigation Specification
10	IF	MINRO	—	—	—	—	—	+3000.00 FT	230.00 KT	—	RNP APCH
20	TF	KD501	—	28(26.5)	—	5.0	—	+3000.00 FT	230.00 KT	—	RNP APCH
10	IF	ARBOX	—	—	—	—	—	+ 3000.00 FT	230.00 KT	—	RNP APCH
20	TF	KD501	—	208(207.0)	—	5.0	—	+ 3000.00 FT	230.00 KT	—	RNP APCH
10	IF	KD501	—	—	—	—	—	+ 3000.00 FT	230.00 KT	—	RNP APCH
20	TF	KD502	—	108(116.7)	—	5.0	—	@2000.00 FT	—	—	RNP APCH
30	TF	RW12	Y	108(116.7)	—	6.0	—	@84.00 FT	—	-3.0/15	RNP APCH
40	FA	RW12	—	108(116.7)	+ 1.0	—	—	—	—	—	RNP APCH
50	DF	KD503	Y	—	—	—	—	—	—	—	RNP APCH
60	DF	SERUR	—	—	—	—	R	+ 3000.00 FT	230.00 KT	—	RNP APCH
70	TF	MINRO	—	332(330.7)	—	17.0	R	+ 3000.00 FT	230.00 KT	—	RNP APCH
70	HM	ARBOX	—	208(207.0)	—	—	L	+ 3000.00 FT	230.00 KT	—	RNP APCH

WAYPOINTS LIST

RNAV GNSS RWY 12

Waypoint Identifier	Coordinates	
ARBOX	04°10'10,8153"N	009°34'54,7791"E
MINRO	04°01'12,6232"N	009°30'24,1002"E
SERUR	03°46'18,1290"N	009°38'43,9250"E
KD501	04°05'41,7227"N	009°32'39,4271"E
KD502	04°03'25,8112"N	009°37'07,4025"E
RWY12	04°00'42,7200"N	009°42'28,9580"E
KD503	03°58'26,7836"N	009°46'56,8938"E