

TABULAR DESCRIPTION

ILS X or LOC X - RWY 05

Serial Number	Path Descriptor	Waypoint Identifier	Fly-Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed limit (Kt)	VPA / TCH	Navigation Specification
10	IF	DIPVA	-					+4000	230	-	RNP APCH
20	TF	TANIS	-	141(140.1)		5.3		+4000	230	-	RNP APCH
10	IF	NAPUX	-					+4000	230	-	RNP APCH
20	TF	TANIS	-	321(320.1)		5.3		+4000	230	-	RNP APCH
10	IF	TANIS	-					+4000	230	-	N/A
20	TF	BB501	-	051(050.1)		5.4		@3000	230	-	N/A
30	TF	RW05	Y	051(050.1)	+1.0	6.0		@1078	-	-3/15	N/A
40	DF	BB502	Y			5.0	L		-	-	RNP APCH
50	HM	DIPVA	-					+4000	230	-	RNP APCH

WAYPOINT LIST

ILS X or LOC X - RWY05		
Waypoint Identifier	Coordinates	
DIPVA	04°18'50.3781"S	015°02'17.0946"E
NAPUX	04°27'00.6100"S	015°09'05.5883"E
TANIS	04°22'55.5020"S	015°05'41.3230"E
BB501	04°19'25.1761"S	015°09'51.6163"E
RWY05	04°15'31.5951"S	015°14'29.9258"E
BB502	04°12'18.2118"S	015°18'20.2791"E