



CAT	CAT. 1				LOC				Circling (3)			RVR for take-off CAT A - B - C : 400 CAT D : 400	
	OCA (OCH)	DA	DH	RVR(1)	RVR(2)	OCA (OCH)	MDA MDH	RVR(1)	RVR(2)	OCA (OCH)	MDA MDH		VIS
A	1182 (154)	1230 (200)	550	1000	1298 (270)	1300 (270)	800	1500	1870 (818)	1870 (820)	1500	Timing FAF/THR 6.0 NM KT MIN SEC KT MIN SEC	
B	1194 (166)	1230 (200)	550	1000	1298 (270)	1300 (270)	800	1500	1870 (818)	1870 (820)	1600		
C	1202 (174)	1230 (200)	550	1000	1298 (270)	1300 (270)	800	1600	2079 (1027)	2080 (1030)	2400		
D	1213 (185)	1230 (200)	550	1000	1298 (270)	1300 (270)	1200	1800	2079 (1027)	2080 (1030)	3600		
													90 4 Min 00 140 2 Min 34
													100 3 Min 36 150 2 Min 24
													110 3 Min 16 160 2 Min 15
													120 3 Min 00 170 2 Min 07
													130 2 Min 46 180 2 Min 00

Notes : - (1) With approach lights - (2) Without approach lights - (3) OCH and MDH AAL - Daytime only
- RDH : 15 m
- Minimum temperature : 10° C.