

TABULAR DESCRIPTION

RNAV _(GNSS) RWY 21											
Serial Nr	Path Descriptor	Waypoint Ident.	Fly-Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (ft)	VPA/TCH	Navigation Specification
010	IF	MOKIM	-	-	-	-	-	+3 100	-	-	RNP APCH
020	TF	DETLA	-	298(294.1)	-4.0	5.0	-	+3 100	-	-	RNP APCH
010	IF	BOSKA	-	-	-	-	-	+3 100	-	-	RNP APCH
020	TF	DETLA	-	118(114.0)	-4.0	5.0	-	+3 100	-	-	RNP APCH
010	IF	DETLA	-	-	-	-	-	+3 100	-	-	RNP APCH
020	TF	BK503	-	208(204.0)	-4.0	5.7	-	@3 100	-	-	RNP APCH
030	TF	RW21	Y	208(204.0)	-4.0	5.8	-	@1 249	-	-3.0/15	RNP APCH
010	IF	RW21	-	-	-	-	-	-	-	-	RNP APCH
020	CF	BK504	Y	208(204.0)	-4.0	5.0	R	-	-	-	RNP APCH
030	DF	BOSKA	-	-	-	-	-	+3 100	-230	-	RNP APCH
010	IF	BOSKA	-	-	-	-	-	+3 100	-230	-	RNP APCH
020	HM	BOSKA	-	118(114.0)	-4.0	-	R	+3 100	-230	-	RNP APCH

WAYPOINT LIST

Waypoint	Latitude	Longitude	Fix name	Notes
MOKIM	07°53'41.3"N	004°54'43.4"W	IAF Left hand base	
DETLA	07°55'44.1"N	004°59'19.5"W	IAF Central	
BOSKA	07°57'46.9"N	005°03'55.6"W	IAF Right hand base	
BK503	07°50'29.3"N	005°01'40.3"W	FAF/FAP	
RW21	07°45'08.9"N	005°04'03.6"W	MAPt	
BK504	07°40'33.6"N	005°06'06.6"W	MATF	

AMDT 03/22 : Magnetic variation and bearing, call sign, Holding