

TABULAR DESCRIPTION

RNAV _(GNSS) RWY 06											
Serial Nr	Path Descriptor	Waypoint Ident.	Fly-Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (ft)	VPA/TCH	Navigation Specification
010	IF	ANUSA	-	-	-	-	-	+4 100	-	-	RNP APCH
020	TF	DENOT	-	147(142.6)	-4.3	5.0	-	+4 100	-	-	RNP APCH
010	IF	MILDA	-	-	-	-	-	+4 100	-	-	RNP APCH
020	TF	DENOT	-	327(322.6)	-4.3	5.0	-	+4 100	-	-	RNP APCH
010	IF	DENOT	-	-	-	-	-	+4 100	-	-	RNP APCH
020	TF	OD501	-	057(052.6)	-4.3	5.8	-	@3 200	-	-	RNP APCH
030	TF	RW06	Y	057(052.6)	-4.3	5.6	-	@1 414	-	-3.0/15	RNP APCH
010	IF	RW06	-	-	-	-	-	-	-	-	RNP APCH
020	CF	OD502	Y	057(052.6)	-4.3	5.0	R	-	-230	-	RNP APCH
030	DF	MILDA	-	-	-	-	-	+4 100	-230	-	RNP APCH
010	IF	MILDA	-	-	-	-	-	+4 100	-230	-	RNP APCH
020	HM	MILDA	-	327(322.6)	-4.3	-	R	+4 100	-230	-	RNP APCH

WAYPOINT LIST

Waypoint	Latitude	Longitude	Fix name	Notes
ANUSA	09°29'05.5"N	007°46'20.6"W	IAF Left hand base	
DENOT	09°25'06.0"N	007°43'16.4"W	IAF Central	
MILDA	09°21'06.4"N	007°40'12.2"W	IAF Right hand base	
OD501	09°28'36.3"N	007°38'38.8"W	FAF/FAP	
RW06	09°32'01.5"N	007°34'08.0"W	MAPt	
OD502	09°35'04.4"N	007°30'06.6"W	MATF	

AMDT 08/21: Missed approach (Serial Nr 30) altitude, Holding