

TABULAR DESCRIPTION

RNP RWY 26

Serial Number	Path Descriptor	Waypoint Identifier	Fly- Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed limit (Kt)	VPA / TCH	Navigation Specification
10	IF	MOKIL	-					+4100	-180	-	RNP APCH
20	TF	AMTUK	-	170(169.4)		5.0		+4100	-180	-	RNP APCH
10	IF	TUPIT	-					+4100	-180	-	RNP APCH
20	TF	AMTUK	-	350(349.4)		5.0		+4100	-180	-	RNP APCH
10	IF	AMTUK	-					+4100	-180	-	RNP APCH
20	TF	GL503	-	260(259.4)		5.5		@3000	-	-	RNP APCH
30	TF	RW26	Y	260(259.4)	+1.0	7.4		@656	-	-3/15	RNP APCH
40	CF	GL504	Y	260(259.4)			L	-	-180	-	RNP APCH
50	DF	TUPIT	-					+4100	-180	-	RNP APCH
10	IF	AMTUK	-					+4100	-170	-	RNP APCH
20	HM	AMTUK	Y	260(259.4)			L	+4100	-170	-	RNP APCH

RNP RWY 26		
Waypoint Identifier	Coordinates	
MOKIL	02°05'31.866"S	011°41'21.418"E
AMTUK	02°10'28.176"S	011°42'16.659"E
TUPIT	02°15'24.485"S	011°43'11.906"E
GL503	02°11'29.300"S	011°36'52.661"E
RW26	02°12'51.081"S	011°29'38.993"E
GL504	02°13'46.607"S	011°24'44.434"E