

TABULAR DESCRIPTION

RNP RWY 17

Serial Number	Path Descriptor	Waypoint Identifier	Fly-Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed limit (Kt)	VPA / TCH	Navigation Specification
10	IF	MILTU	-					+4200	-230	-	RNP APCH
20	TF	AGPOT	-	078(077.4)		5.0		+4200	-230	-	RNP APCH
10	IF	PISLU	-					+4600	-230	-	RNP APCH
20	TF	AGPOT	-	258(257.4)		5.0		+4200	-230	-	RNP APCH
10	IF	AGPOT	-					+4200	-230	-	RNP APCH
20	TF	GM501	-	168(167.4)		5.0		@3100	-	-	RNP APCH
30	TF	RW17	Y	168(167.4)	+1.0	8.7		@329	-	-3/15	RNP APCH
40	CF	GM502	Y	168(167.4)			R	-	-	-	RNP APCH
50	DF	MILTU	-					+4200	-230	-	RNP APCH
10	IF	AGPOT	-					+4200	-230	-	RNP APCH
20	HM	AGPOT	Y	168(167.4)			R	+4200	-230	-	RNP APCH

RNP RWY 17		
Waypoint Identifier	Coordinates	
MILTU	01°37'52.514"S	010°55'26.117"E
AGPOT	01°36'46.875"S	011°00'18.512"E
PISLU	01°35'41.224"S	011°05'10.902"E
GM501	01°41'41.119"S	011°01'23.746"E
RW17	01°50'13.375"S	011°03'17.328"E
GM502	01°55'07.617"S	011°04'22.578"E