



CAT	LNAV/VNAV			LNAV			Circling (*)				RVR for take-off
	OCA (OCH)	MDA MDH	RVR	OCA (OCH)	MDA MDH	RVR	OCA (OCH)	MDA MDH	VIS	CAT A - B - C : 400	
A	505 (470)	510 (470)	1500	837 (802)	840 (810)	1500	886 (799)	890 (800)	1500	CAT D : 400	
B	517 (482)	520 (490)	1500	837 (802)	840 (810)	1500	906 (819)	910 (820)	1600		
C	537 (502)	540 (510)	2000	837 (802)	840 (810)	2000	1005 (918)	1010 (920)	2400		
D	564 (529)	570 (530)	2000	837 (802)	840 (810)	2000	1005 (918)	1010 (920)	3600		

**Notes :** - (\*) Daytime only, OCH and MDH AAL.  
 - Climbing sectors after take-off: Between radials 017° MG and 283° MG  
 - Minimum temperature: 15°

**Timing** FAF / THR 7.9 NM

KT	MIN	SEC	KT	MIN	SEC
90	5	16	140	3	23
100	4	44	150	3	10
110	4	19	160	2	58
120	3	57	170	2	47
130	3	39	180	2	38

**PROCEDURE TO BE USED ACCORDING TO AIC NR 09/A/14 FM - 06 NOVEMBER 2014**

AMDT 12/18: NORMALISATION