

TABULAR DESCRIPTION

RNP RWY 27L

Serial Number	Path Descriptor	Waypoint Identifier	Fly- Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed limit (Kt)	VPA / TCH	Navigation Specification
10	IF	MOVID	-					+2500	230	-	RNP APCH
20	TF	LILAM	-	178(177.3)		6.0		+2500	230	-	RNP APCH
10	IF	KELUT	-					+2500	230	-	RNP APCH
20	TF	LILAM	-	358(357.3)		6.0		+2500	230	-	RNP APCH
10	IF	LILAM	-					+2500	230	-	RNP APCH
20	TF	RN503	-	268(267.3)		6.6		@2500		-	RNP APCH
30	TF	RW27L	Y	268(267.3)	+1.0	5.5		@753	-	-3/15	RNP APCH
40	TF	RN504	Y	268(267.3)		5.0	L				RNP APCH
50	DF	KELUT	-					+2500			
10	IF	LILAM	-					+2500	230	-	RNP APCH
20	HM	LILAM	Y	268(267.3)			L	+2500	230	-	RNP APCH

RNP RWY 27L		
Waypoint Identifier	Coordinates	
MOVID	13°35'34.873"N	002°24'23.623"E
LILAM	13°29'33.700"N	002°24'41.100"E
KELUT	13°23'32.524"N	002°24'58.562"E
RN503	13°29'15.159"N	002°17'53.737"E
RW27L	13°28'59.640"N	002°12'16.200"E
RN504	13°28'45.389"N	002°07'08.653"E