



CAT	LNAV/VNAV				LNAV				Circling (3)				RVR for take-off			
	OCA (OCH)	DA	DH	RVR(1) RVR(2)	OCA (OCH)	MDA MDH	RVR(1) RVR(2)	OCA (OCH)	MDA MDH	VIS	CAT A - B - C	CAT D				
A	491 (219)	500 (250)	600	1000	635 (363)	640 (370)	900 1500	766 (476)	770 (740)	1500			Temps FAF / THR 8.4 NM			
B	503 (231)	510 (260)	600	1000	635 (363)	640 (370)	1000 1500	837 (547)	840 (740)	1600			90	5 Min 36	140	3 Min 36
C	520 (248)	520 (270)	600	1000	635 (363)	640 (370)	1000 1800	947 (657)	950 (830)	2400			100	5 Min 02	150	3 Min 22
D	547 (275)	530 (280)	600	1000	635 (363)	640 (370)	1400 2000	947 (657)	950 (830)	3600			110	4 Min 35	160	3 Min 09
Notes : - (1) With approach lights - (2) Without approach lights - (3) Minimum temperature : 10°C - (4) Daytime only - OCH and MDH AAL.											120	4 Min 12	170	2 Min 58		
											130	3 Min 53	180	2 Min 48		

AMDT10/22 : Update