



CAT	CAT.1				LOC X				Circling (3)				RVR for take-off CAT A - B - C : 400 CAT D : 400		
	OCA (OCH)	DA	DH	RVR(1)	RVR(2)	OCA (OCH)	MDA	MDH	RVR(1)	RVR(2)	OCA (OCH)	MDA		MDH	VIS
A	458 (186)	480 (200)	550	1000	574 (302)	580 (310)	900	1500	766 (476)	770 (740)	1500	Temps FAF / THR 8.4 NM			
B	470 (198)	480 (200)	550	1000	574 (302)	580 (310)	1000	1500	837 (547)	840 (740)	1600	90	5 Min 36	140	3 Min 36
C	478 (206)	480 (210)	600	1000	574 (302)	580 (310)	1000	1800	947 (657)	950 (830)	2400	100	5 Min 02	150	3 Min 22
D	489 (217)	490 (220)	600	1000	574 (302)	580 (310)	1400	2000	947 (657)	950 (830)	3600	110	4 Min 35	160	3 Min 09
												120	4 Min 12	170	2 Min 58
												130	3 Min 53	180	2 Min 48

Notes: (1) With approach lights - (2) Without approach lights - (3) Daytime only - OCH and MDH AAL

AMDT 12/18: NORMALIZATION